

**Carrier**  
**XPOWERMULTI**  
INVERTER

Ductless Multi Split  
Continuous Comfort. Endless Options.



# Smart Comfort. Superior Performance.

Carrier's Xpower Multi Split System will deliver the ultimate cooling and heating comfort with the maximum flexibility.



**Energy Efficient** — DC Inverter technology with twin rotary compressor and DC fan motor, allows systems to achieve excellent energy efficiencies up to 20 SEER.

**Space-saving Installation** — Up to five indoor units can be connected to a single outdoor unit, reducing the number of outdoor units required. All indoor units can be individually controlled and do not need to be installed at the same time.



**Application Flexibility** — Long piping design for a wide choice of installation sites.

**Personalized Comfort Control** — Enjoy separate comfort settings on the indoor units with individual remote controls.

**Quiet Operation** — Ideal for spaces where people spend large amounts of time, and need low sound levels.



**Environmentally Friendly** — Washable filters on indoor units and the use of R410A refrigerant reduce harmful effects on the earth.

**Built to last** — The outdoor unit is built to last with a golden anti-corrosive treatment, which prolongs the unit's performance and sustains the most severe climates.

# TECHNICAL SPECIFICATIONS

## Outdoor Units



### INVERTER CONDENSER-COOLING ONLY

| Outdoor Model                               |                   | 38KUS018DS2                | 38KUS027DS3                | 38KUS036DS4  | 38KUS042DS5  |
|---|-------------------|----------------------------|----------------------------|--|--|
| Power supply                                | V-ph-Hz           | 208-230V~, 50/60Hz, 1Ph    | 208-230V~, 50/60Hz, 1Ph    | 208-230V~, 50/60Hz, 1Ph  | 208-230V~, 50/60Hz, 1Ph  |
| Rating Capacity(Range)                      | Btu/h             | 18000(10000-19000)         | 27000(19000-28000)         | 36000(19000-37000)   | 42000(19000-43000)   |
| Rating Current(Range)                       | A                 | 7.1(3.4-8.3)               | 10.9(6.1-13.0)             | 16.1(9.3-16.5)   | 17.6(6.2-18.1)   |
| Rating Input                                | W                 | 1650                       | 2400                       | 3600   | 3950   |
| Max current                                 | A                 | 10                         | 15                         | 21.5   | 23   |
| Max input                                   | W                 | 2100                       | 3100                       | 4600   | 4800   |
| EER   | W/W               | 3.2                        | 3.3                        | 2.9  | 3.1  |
| SEER  |                   | 20                         | 20                         | 20   | 20   |
| Outdoor air flow                            | m <sup>3</sup> /h | 2700                       | 2700                       | 4000   | 4000   |
| Outdoor sound pressure level                | dB(A)             | 59                         | 60                         | 62   | 62   |
| Throttle type                               |                   | Capillary+EXV              |                            |  |  |
| Dimension(W*D*H)                            | mm                | 845x363x702                | 845x363x702                | 946x410x810  | 946x410x810  |
| Packing(W*D*H)                              | mm                | 965x395x755                | 965x395x755                | 1090x500x865   | 1090x500x865   |
| Net/Gross weight                            | kg                | 45/48                      | 49/52                      | 68/73  | 72/77  |
| Refrigerant charge amount, R410A            | kg                | 1.1                        | 1.25                       | 2.6  | 3.3  |
| Design pressure                             | MPa               | 4.2/1.5                    |                            |  |  |
| Refrigerant piping (Liquid side/ Gas side)  | mm(inch)          | 2 x Φ6.35/Φ9.52(1/4"/3/8") | 3 x Φ6.35/Φ9.52(1/4"/3/8") | 3 x Φ6.35/Φ9.52(1/4"/3/8")<br>1 x Φ6.35/Φ12.7(1/4"/1/2")   | 4 x Φ6.35/Φ9.52(1/4"/3/8")<br>1 x Φ6.35/Φ12.7(1/4"/1/2")   |
| Additional Adapters in CDU                  | mm(inch)          | 1 x Φ9.52-Φ12.7(3/8"-1/2") | 1 x Φ9.52-Φ12.7(3/8"-1/2") | 1 x Φ6.35-Φ9.52(1/4"-3/8")<br>1 x Φ9.52-Φ12.7(3/8"-1/2")<br>1 x Φ12.7-Φ15.9(1/2"-5/8")<br>1 x Φ12.7-Φ9.52(1/2"-3/8") | 1 x Φ6.35-Φ9.52(1/4"-3/8")<br>1 x Φ9.52-Φ12.7(3/8"-1/2")<br>1 x Φ12.7-Φ15.9(1/2"-5/8")<br>1 x Φ12.7-Φ9.52(1/2"-3/8") |
| Max. length for all rooms                   | m                 | 30                         | 45                         | 60   | 60   |
| Max. length for one indoor unit             | m                 | 20                         | 25                         | 30   | 30   |
| Max. height difference between IDU and CDU  | m                 | 10                         |                            |  |  |
| Max. height difference between indoor units | m                 | 10                         |                            |  |  |
| Temp range cooling                          | °C                | -10-46                     |                            |  |  |
| Compressor                                  | Model             | ASM135D23UFZ               | ATF235D22UMT               | ATF250D22UMT   | ATF310D43UMT   |
|   | Type              | Dual Rotary                |                            |  |  |
|   | Brand             | GMCC                       |                            |  |  |

# Outdoor Units



## HEAT PUMP INVERTER CONDENSER

| Outdoor Model                               |          | 38QUS018DS2-1              | 38QUS027DS3-1              | 38QUS036DS4-1  | 38QUS042DS5-1  |
|---|----------|----------------------------|----------------------------|--|--|
| Power supply                                | V-ph-Hz  | 208-230V~, 50/60Hz, 1Ph    | 208-230V~, 50/60Hz, 1Ph    | 208-230V~, 50/60Hz, 1Ph  | 208-230V~, 50/60Hz, 1Ph  |
| Rating Capacity (Cooling/ Heating)(Range)   | Btu/h    | 18000/19000(10000-19000)   | 27000/28000(19000-28000)   | 36000/38000(19000-38000)   | 42000/42000(19000-43000)   |
| Rating Current (Cooling/Heating)(Range)     | A        | 7.3/6.8(3.4-8.3)           | 11.5/10.6(6.1-13.0)        | 16.6/13.7(9.3-17.2)  | 17/15.2(6.2-18.1)  |
| Rating Input (Cooling/Heating)              | W        | 1650/1530                  | 2570/2350                  | 3800/3110  | 3900/3465  |
| EER / COP                                   | W/W      | 3.2/3.6                    | 3.1/3.6                    | 2.8/3.5  | 3.2/3.5  |
| SEER  |          | 20                         | 20                         | 20   | 20   |
| Max current                                 | A        | 12                         | 16                         | 21.5   | 22   |
| Max input                                   | W        | 2300                       | 3300                       | 4600   | 4700   |
| Outdoor air flow                            | m3/h     | 2700                       | 2700                       | 4000   | 4000   |
| Outdoor sound pressure level                | dB(A)    | 59.5                       | 59.5                       | 63   | 63   |
| Throttle type                               |          | Capillary+EXV              | Capillary+EXV              | Capillary+EXV  | Capillary+EXV  |
| Dimension(W*D*H)                            | mm       | 845x363x702                | 845x363x702                | 946x410x810  | 946x410x810  |
| Packing(W*D*H)                              | mm       | 965x395x755                | 965x395x755                | 1090x500x865   | 1090x500x865   |
| Net/Gross weight                            | kg       | 48.5/52                    | 52.5/56                    | 70/75  | 76/81  |
| Refrigerant charge amount, R410A            | kg       | 1.9                        | 2.1                        | 3.0  | 3.6  |
| Design pressure                             | MPa      | 4.2/1.5                    | 4.2/1.5                    | 4.2/1.5  | 4.2/1.5  |
| Refrigerant piping (Liquid side/ Gas side)  | mm(inch) | 2 x Φ6.35/Φ9.52(1/4"/3/8") | 3 x Φ6.35/Φ9.52(1/4"/3/8") | 3 x Φ6.35/Φ9.52(1/4"/3/8")<br>1 x Φ6.35/Φ12.7(1/4"/1/2")   | 4 x Φ6.35/Φ9.52(1/4"/3/8")<br>1 x Φ6.35/Φ12.7(1/4"/1/2")   |
| Additional Adapters in CDU                  | mm(inch) | 1 x Φ9.52-Φ12.7(3/8"-1/2") | 1 x Φ9.52-Φ12.7(3/8"-1/2") | 1 x Φ6.35-Φ9.52(1/4"-3/8")<br>1 x Φ9.52-Φ12.7(3/8"-1/2")<br>1 x Φ12.7-Φ9.52(1/2"-3/8")<br>1 x Φ12.7-Φ15.9(1/2"-5/8") | 1 x Φ6.35-Φ9.52(1/4"-3/8")<br>1 x Φ12.7-Φ9.52(1/2"-3/8")<br>1 x Φ9.52-Φ12.7(3/8"-1/2")<br>1 x Φ12.7-Φ15.9(1/2"-5/8") |
| Max. length for all rooms                   | m        | 30                         | 45                         | 60   | 60   |
| Max. length for one indoor unit             | m        | 20                         | 25                         | 30   | 30   |
| Max. height difference between IDU and CDU  | m        | 10                         | 10                         | 10   | 10   |
| Max. height difference between indoor units | m        | 10                         | 10                         | 10   | 10   |
| Temp range cooling                          | °C       | -10-46                     | -10-46                     | -10-46   | -10-46   |
| Temp range heating                          | °C       | -15-24                     | -15-24                     | -15-24   | -15-24   |
| Compressor                                  | Model    | ASM135D23UFZ               | ATF235D22UMT               | ATF250D22UMT   | ATF310D43UMT   |
|   | Type     | Dual Rotary                | Dual Rotary                | Dual Rotary  | Dual Rotary  |
|   | Brand    | GMCC                       | GMCC                       | GMCC   | GMCC   |

# Indoor Units



## HI WALL COOLING ONLY

| INDOOR UNIT - High Wall 15C                 |                   | 42KHC009DSM             | 42KHC012DSM             | 42KHC018DSM             | 42KHC024DSM             |
|---|-------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| Power supply                                | V-ph-Hz           | 208-230V~, 50/60Hz, 1Ph | 208-230V~, 50/60Hz, 1Ph | 208-230V~, 50/60Hz, 1Ph | 208-230V~, 50/60Hz, 1Ph |
| Capacity                                    | Btu/h             | 9000                    | 12000                   | 18000                   | 22000                   |
| Indoor fan motor input                      | W                 | 22                      | 22                      | 36                      | 60                      |
| Current                                     | Rated current     | 0.2                     | 0.2                     | 0.3                     | 0.3                     |
| Sound pressure level (high/med/low/silence) | dB(A)             | 38/34/30/21             | 40/35/31/22             | 42/37/35/24             | 47/42/38/26             |
| Air flow (high/med/low/silence)             | m <sup>3</sup> /h | 470/390/300/180         | 500/390/300/180         | 600/500/400/260         | 600/500/400/260         |
| Weight (Net/Gross)                          | kg                | 8.0 / 10.5              | 9.0 / 12.0              | 11.5 / 16.5             | 13.5 / 18.5             |
| Dimensions (WxDxH)                          | mm                | 730x192x291             | 812x192x300             | 973x218x319             | 1082x225x338            |
| Packing (W*D*H)                             | mm                | 800x275x375             | 880x275x385             | 1055x405x305            | 1165x420x315            |
| Refrigerant piping (Liquid side/ Gas side)  | mm(inch)          | Φ6.35/Φ9.52 (1/4"/3/8") | Φ6.35/Φ9.52 (1/4"/3/8") | Φ6.35/Φ12.7 (1/4"/1/2") | Φ9.52/Φ15.9 (3/8"/5/8") |



## HI WALL HEAT PUMP

| INDOOR UNIT - High Wall 15C                 |                   | 42QHC009DSM             | 42QHC012DSM             | 42QHC018DSM             | 42QHC024DSM             |
|---|-------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| Power supply                                | V-ph-Hz           | 208-230V~, 50/60Hz, 1Ph | 208-230V~, 50/60Hz, 1Ph | 208-230V~, 50/60Hz, 1Ph | 208-230V~, 50/60Hz, 1Ph |
| Capacity                                    | Btu/h             | 9000                    | 12000                   | 18000                   | 22000                   |
| Indoor fan motor input                      | W                 | 22                      | 22                      | 36                      | 60                      |
| Current                                     | Rated current     | 0.2                     | 0.2                     | 0.3                     | 0.3                     |
| Sound pressure level (high/med/low/silence) | dB(A)             | 38/34/30/21             | 40/35/31/22             | 42/37/35/24             | 47/42/38/26             |
| Air flow (high/med/low/silence)             | m <sup>3</sup> /h | 470/390/300/180         | 500/390/300/180         | 600/500/400/260         | 600/500/400/260         |
| Weight (Net/Gross)                          | kg                | 8.0 / 10.5              | 9.0 / 12.0              | 11.5 / 16.5             | 13.5 / 18.5             |
| Dimensions (WxDxH)                          | mm                | 730x192x291             | 812x192x300             | 973x218x319             | 1082x225x338            |
| Packing (W*D*H)                             | mm                | 800x275x375             | 880x275x385             | 1055x405x305            | 1165x420x315            |
| Refrigerant piping (Liquid side/ Gas side)  | mm(inch)          | Φ6.35/Φ9.52 (1/4"/3/8") | Φ6.35/Φ9.52 (1/4"/3/8") | Φ6.35/Φ12.7 (1/4"/1/2") | Φ9.52/Φ15.9 (3/8"/5/8") |



## CASSETTE

| Model                                    |                   | 42QTD009DS-1            | 42QTD012DS-1            | 42QTD018DS-1            | 42QTD024DS-1            |
|--|-------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| Power supply                             | V-ph-Hz           | 208-230V~, 50/60Hz, 1Ph | 208-230V~, 50/60Hz, 1Ph | 208-230V~, 50/60Hz, 1Ph | 208-230V~, 50/60Hz, 1Ph |
| Capacity                                 | Btu/h             | 9000                    | 12000                   | 18000                   | 24000                   |
| Input                                    | W                 | 40                      | 40                      | 40                      | 120                     |
| Current                                  | A                 | 0.18                    | 0.18                    | 0.18                    | 0.53                    |
| Indoor air flow                          | m <sup>3</sup> /h | 580/500/450             | 650/550/460             | 680/560/500             | 1520/1350/1200          |
| Indoor sound pressure level              | dB(A)             | 39/36/33.5              | 44/41/39                | 44/42/41                | 48/46/43                |
| Dimension (W x Dx H)(body)               | mm                | 570x570x260             | 570x570x260             | 570x570x260             | 840x840x245             |
| Packing (W x Dx H)(body)                 | mm                | 655x655x290             | 655x655x290             | 655x655x290             | 900x900x257             |
| Dimension (W x Dx H)(panel)              | mm                | 647x647x50              | 647x647x50              | 647x647x50              | 950x950x55              |
| Packing (W x Dx H)(panel)                | mm                | 715x715x123             | 715x715x123             | 715x715x123             | 1035x1035x90            |
| Net/Gross weight(body)                   | kg                | 14.5/17.3               | 14.4/17.2               | 16.1/18.9               | 24/28                   |
| Net/Gross weight                         | kg                | 2.5/4.5                 | 2.5/4.5                 | 2.5/4.5                 | 5/8                     |
| Design pressure                          | MPa               | 4.2/1.5                 | 4.2/1.5                 | 4.2/1.5                 | 4.2/1.5                 |
| Drainage water pipe dia.                 | mm                | ODΦ25                   | ODΦ25                   | ODΦ25                   | ODΦ32                   |
| Refrigerant piping Liquid side/ Gas side | mm                | Φ6.35/Φ9.52(1/4"/3/8")  | Φ6.35/Φ9.52(1/4"/3/8")  | Φ6.35/Φ12.7(1/4"/1/2")  | Φ9.52/Φ15.9(3/8"/5/8")  |
| Controller                               |                   | Remote control          | Remote control          | Remote control          | Remote control          |
| Room temperature                         | Cooling           | °C                      | 17-32                   | 17-32                   | 17-32                   |
|  | Heating           | °C                      | 0-30                    | 0-30                    | 0-30                    |
| Operation temperature                    | °C                | 17-30                   | 17-30                   | 17-30                   | 17-30                   |

# Indoor Units



## FLOORCEILING

| Model                       |                       |    | 42QZA009DS              | 42QZA012DS              | 42QZA018DS              |
|-----------------------------|-----------------------|----|-------------------------|-------------------------|-------------------------|
| Power supply                | V-ph-Hz               |    | 208-230V~, 50/60Hz, 1Ph | 208-230V~, 50/60Hz, 1Ph | 208-230V~, 50/60Hz, 1Ph |
| Capacity                    | Btu/h                 |    | 9000                    | 12000                   | 18000                   |
| Input                       | W                     |    | 30                      | 40                      | 58                      |
| Current                     | A                     |    | 0.13                    | 0.17                    | 0.25                    |
| Indoor air flow             | m <sup>3</sup> /h     |    | 710/680/580/450         | 710/680/580/450         | 820/740/650/520         |
| Indoor sound pressure level | dB(A)                 |    | 45/40/35                | 46/40/34                | 48/44/39                |
| Indoor unit                 | Dimension (W x Dx H)  | mm | 700x600x210             |                         |                         |
|                             | Packing (W x Dx H)    | mm | 810x710x305             |                         |                         |
|                             | Net/Gross weight      | kg | 13.5/18                 | 15/20                   | 15/20                   |
| Design pressure             | MPa                   |    | 4.2/1.5                 |                         |                         |
| Drainage water pipe dia.    | mm                    |    | ODΦ16                   |                         |                         |
| Refrigerant piping          | Liquid side/ Gas side | mm | Φ6.35/Φ9.52(1/4"/3/8")  | Φ6.35/Φ9.52(1/4"/3/8")  | Φ6.35/Φ12.7(1/4"/1/2")  |
| Controller                  |                       |    | Remote control          |                         |                         |
| Room temperature            | Cooling               | °C | 17-32                   |                         |                         |
|                             | Heating               | °C | 0-30                    |                         |                         |
| Operation temperature       |                       | °C | 17-30                   |                         |                         |



## SLIM DUCT FAN COIL

| Model                       |                       |    | 42QSS012DS-1            | 42QSS018DS-1            | 42QSS024DS-1            |
|-----------------------------|-----------------------|----|-------------------------|-------------------------|-------------------------|
| Power supply                | V-ph-Hz               |    | 208-230V~, 50/60Hz, 1Ph | 208-230V~, 50/60Hz, 1Ph | 208-230V~, 50/60Hz, 1Ph |
| Capacity                    | Btu/h                 |    | 12000                   | 18000                   | 24000                   |
| Input                       | W                     |    | 60                      | 160                     | 160                     |
| Current                     | A                     |    | 0.3                     | 0.8                     | 0.8                     |
| Indoor air flow             | m <sup>3</sup> /h     |    | 680/580/450             | 850/725/570             | 1200/1000/850           |
| Indoor sound pressure level | dB(A)                 |    | 42/38/35                | 42/40/36                | 44/42/37                |
| Indoor unit                 | Dimension (W x Dx H)  | mm | 700x635x210             | 880x674x210             | 1100x774x249            |
|                             | Packing (W x Dx H)    | mm | 915x655x290             | 1070x725x270            | 1305x805x305            |
|                             | Net/Gross weight      | kg | 18.4/22.7               | 23.5/29                 | 31/38                   |
| Design pressure             | MPa                   |    | 4.2/1.5                 | 4.2/1.5                 | 4.2/1.5                 |
| Drainage water pipe dia.    | mm                    |    | ODΦ25                   | ODΦ25                   | ODΦ25                   |
| Refrigerant piping          | Liquid side/ Gas side | mm | Φ6.35/Φ9.52(1/4"/3/8")  | Φ6.35/Φ12.7(1/4"/1/2")  | Φ9.52/Φ15.9(3/8"/5/8")  |
| Controller                  |                       |    | Wired control           | Wired control           | Wired control           |
| Room temperature            | Cooling               | °C | 17-32                   | 17-32                   | 17-32                   |
|                             | Heating               | °C | 0-30                    | 0-30                    | 0-30                    |
| Operation temperature       |                       | °C | 17-30                   | 17-30                   | 17-30                   |

# Combinations & Capacities

| OUTDOOR UNIT MODEL             |              | COOLING CAPACITY (Btu/h) |        |        |        |       |
|--------------------------------|--------------|--------------------------|--------|--------|--------|-------|
| 38KUS018DS2<br>(18K 1 drive 2) |              | IDU 1                    | IDU 2  | IDU 3  | IDU 4  | IDU 5 |
| 9K+9K                          | 2 ---<br>IDU | 9,000                    | 9,000  |        |        |       |
| 9K+12K                         |              | 8,500                    | 10,500 |        |        |       |
| 12K+12K                        |              | 9,500                    | 9,500  |        |        |       |
| 38KUS027DS3<br>(27K 1 drive 3) |              | IDU 1                    | IDU 2  | IDU 3  | IDU 4  | IDU 5 |
| 9K+9K                          | 2 ---<br>IDU | 9,500                    | 9,500  |        |        |       |
| 9K+12K                         |              | 9,500                    | 12,000 |        |        |       |
| 9K+18K                         |              | 8,400                    | 16,600 |        |        |       |
| 12K+12K                        |              | 12,000                   | 12,000 |        |        |       |
| 12K+18K                        |              | 10,000                   | 15,000 |        |        |       |
| 9+9+9                          | 3 ---<br>IDU | 9,000                    | 9,000  | 9,000  |        |       |
| 9+9+12                         |              | 8,500                    | 8,500  | 11,000 |        |       |
| 9+9+18                         |              | 8,000                    | 8,000  | 12,000 |        |       |
| 9+12+12                        |              | 8,000                    | 10,000 | 10,000 |        |       |
| 12+12+12                       |              | 9,500                    | 9,500  | 9,500  |        |       |
| 38KUS036DS4<br>(36K 1 drive 4) |              | IDU 1                    | IDU 2  | IDU 3  | IDU 4  | IDU 5 |
| 9+9                            | 2 ---<br>IDU | 9,500                    | 9,500  |        |        |       |
| 9+12                           |              | 9,500                    | 12,000 |        |        |       |
| 9+18                           |              | 9,500                    | 17,500 |        |        |       |
| 12+12                          |              | 12,000                   | 12,000 |        |        |       |
| 12+18                          |              | 12,000                   | 18,000 |        |        |       |
| 18+18                          |              | 16,500                   | 16,500 |        |        |       |
| 9+24                           |              | 8,500                    | 22,500 |        |        |       |
| 12+24                          |              | 10,500                   | 21,000 |        |        |       |
| 9+9+9                          | 3 ---<br>IDU | 9,333                    | 9,333  | 9,333  |        |       |
| 9+9+12                         |              | 9,000                    | 9,000  | 12,000 |        |       |
| 9+9+18                         |              | 8,000                    | 8,000  | 16,000 |        |       |
| 9+9+24                         |              | 8,000                    | 8,000  | 21,000 |        |       |
| 9+12+12                        |              | 8,500                    | 11,500 | 11,500 |        |       |
| 9+12+18                        |              | 8,000                    | 11,000 | 15,000 |        |       |
| 9+12+24                        |              | 8,000                    | 10,000 | 20,000 |        |       |
| 9+18+18                        |              | 8,000                    | 14,000 | 14,000 |        |       |
| 12+12+12                       |              | 11,333                   | 11,333 | 11,333 |        |       |
| 12+12+18                       |              | 11,000                   | 11,000 | 14,000 |        |       |
| 9+9+9+9                        | 4 ---<br>IDU | 9,000                    | 9,000  | 9,000  | 9,000  |       |
| 9+9+9+12                       |              | 8,500                    | 8,500  | 8,500  | 11,500 |       |
| 9+9+9+18                       |              | 8,000                    | 8,000  | 8,000  | 14,000 |       |
| 9+9+12+12                      |              | 8,000                    | 8,000  | 10,500 | 10,500 |       |
| 9+9+12+18                      |              | 7,500                    | 7,500  | 9,000  | 14,000 |       |
| 9+12+12+12                     |              | 7,000                    | 10,000 | 10,000 | 10,000 |       |
| 9+12+12+18                     |              | 7,000                    | 10,000 | 10,000 | 12,500 |       |
| 12+12+12+12                    |              | 9,500                    | 9,500  | 9,500  | 9,500  |       |
| 12+12+12+18                    |              | 9,500                    | 9,500  | 9,500  | 12,000 |       |

| OUTDOOR UNIT MODEL           |              | COOLING CAPACITY (Btu/h) |        |        |        |        |
|------------------------------|--------------|--------------------------|--------|--------|--------|--------|
| 38KUS042DS5<br>(42K drive 5) |              | Zone 1                   | Zone 2 | Zone 3 | Zone 4 | Zone 5 |
| 9+9                          | 2 ---<br>IDU | 9,500                    | 9,500  |        |        |        |
| 9+12                         |              | 9,500                    | 12,000 |        |        |        |
| 9+18                         |              | 9,500                    | 18,500 |        |        |        |
| 9+24                         |              | 9,000                    | 23,000 |        |        |        |
| 12+12                        |              | 12,000                   | 12,000 |        |        |        |
| 12+18                        |              | 12,000                   | 18,000 |        |        |        |
| 12+24                        |              | 12,000                   | 23,000 |        |        |        |
| 18+18                        |              | 18,500                   | 18,500 |        |        |        |
| 18+24                        |              | 17,500                   | 22,500 |        |        |        |
| 9+9+9                        |              | 9,500                    | 9,500  | 9,500  |        |        |
| 9+9+12                       | 9,500        | 9,500                    | 12,000 |        |        |        |
| 9+9+18                       | 9,500        | 9,500                    | 18,000 |        |        |        |
| 9+9+24                       | 9,000        | 9,000                    | 22,500 |        |        |        |
| 9+12+12                      | 9,500        | 12,500                   | 12,500 |        |        |        |
| 9+12+18                      | 9,000        | 12,000                   | 18,000 |        |        |        |
| 9+12+24                      | 9,000        | 12,000                   | 21,500 |        |        |        |
| 9+18+18                      | 8,000        | 16,000                   | 16,000 |        |        |        |
| 12+12+12                     | 12,000       | 12,000                   | 12,000 |        |        |        |
| 12+12+18                     | 12,000       | 12,000                   | 17,000 |        |        |        |
| 12+12+24                     | 11,000       | 11,000                   | 21,000 |        |        |        |
| 12+18+18                     | 11,000       | 16,000                   | 16,000 |        |        |        |
| 9+9+9+9                      | 9,250        | 9,250                    | 9,250  | 9,250  |        |        |
| 9+9+9+12                     | 9,000        | 9,000                    | 9,000  | 12,000 |        |        |
| 9+9+9+18                     | 8,500        | 8,500                    | 8,500  | 16,000 |        |        |
| 9+9+9+24                     | 8,000        | 8,000                    | 8,000  | 18,000 |        |        |
| 9+9+12+12                    | 9,000        | 9,000                    | 12,000 | 12,000 |        |        |
| 9+9+12+18                    | 8,000        | 8,000                    | 11,000 | 16,000 |        |        |
| 9+9+12+24                    | 7,500        | 7,500                    | 10,000 | 18,000 |        |        |
| 9+12+12+12                   | 8,000        | 11,000                   | 11,000 | 11,000 |        |        |
| 9+12+12+18                   | 7,500        | 10,000                   | 10,000 | 14,000 |        |        |
| 12+12+12+12                  | 10,000       | 10,000                   | 10,000 | 10,000 |        |        |
| 12+12+12+18                  | 9,500        | 9,500                    | 9,500  | 14,000 |        |        |
| 9+9+9+9+9                    | 8,500        | 8,500                    | 8,500  | 8,500  | 8,500  |        |
| 9+9+9+9+12                   | 8,000        | 8,000                    | 8,000  | 8,000  | 11,000 |        |
| 9+9+9+9+18                   | 7,500        | 7,500                    | 7,500  | 7,500  | 13,000 |        |
| 9+9+9+12+12                  | 7,500        | 7,500                    | 7,500  | 10,000 | 10,000 |        |
| 9+9+9+12+18                  | 7,000        | 7,000                    | 7,000  | 10,000 | 12,000 |        |
| 9+9+12+12+12                 | 7,000        | 7,000                    | 9,500  | 9,500  | 9,500  |        |
| 9+12+12+12+12                | 7,000        | 9,000                    | 9,000  | 9,000  | 9,000  |        |
| 9+12+12+12+18                | 6,500        | 8,000                    | 8,000  | 8,000  | 12,000 |        |
| 12+12+12+12+12               | 8,500        | 8,500                    | 8,500  | 8,500  | 8,500  |        |

\*IDU - Indoor Unit



**A Century of Innovation.**

Built on Willis Carrier's invention of modern air conditioning in 1902, Carrier is the world leader in heating, air-conditioning and refrigeration solutions. We constantly build upon our history of proven innovation with new products and services that improve global comfort and efficiency. Carrier Ductless Systems deliver efficiency, performance and control thanks to advanced technology. When it comes to creating comfort, one size or system may not fit all, but one name does: **Carrier**.

[www.carriercca.com](http://www.carriercca.com)